

3M Novec™ 71DA

Engineered Fluid

Introduction

3M™ Novec™ 71DA Engineered Fluid is a hydrofluoroether, Methyl Nonafluorobutyl Ether (C₄F₉OCH₃), in an azeotrope formulation with trans-1,2-dichloroethylene (t-DCE) and ethanol. This mixture is a true azeotrope, with constant vapor and liquid composition at its boiling point.

Novec 71DA fluid is ideal for defluxing and degreasing tasks and is intended to replace ozone-depleting materials in many applications as well as certain aqueous cleaning processes and solvent coating applications. This Novec product has zero ozone depletion potential and other favorable environmental properties (see Table 2). Novec 71DA fluid has a recommended time-weighted average exposure guideline of 750 ppm for the 3M™ Novec™ 7100 Engineered Fluid component (eight hour average), 200 ppm for trans-1,2-dichloroethylene (t-DCE) and 1000 ppm for ethyl alcohol. These exposure guidelines suggest there is a large margin of safety for use of Novec 71DA fluid in its intended cleaning applications.

The increased solvency and low surface tension, nonflammability and constant composition during boiling of Novec 71DA fluid make it ideal for immersion defluxing and degreasing applications. The ethanol component of Novec 71DA fluid provides enhanced removal of ionic contaminants.

Typical Applications

Cleaning, rinsing and drying agent; coating solvent

- Cleaning of oils, greases, waxes, handling oils and solder flux residue
- Precision coating of silicones and other lubricants

For information on other typical applications, contact your 3M representative or 3M authorized specialty fluids distributor.

Material Description

Ingredients	Novec 71DA
Methyl Nonafluorobutyl Ether (C ₄ F ₉ OCH ₃)	52.7% by weight
Trans-1,2-dichloroethylene (t-DCE)	44.6% by weight
Ethanol	2.7% by weight
Appearance	Clear, colorless

¹Novec 71DA fluid (C₄F₉OCH₃) consists of two inseparable isomers with essentially identical properties. These are (CF₃)₂CFCH₂OCH₃ (CAS No. 163702-08-7) and CF₃CF₂CF₂OCH₃ (CAS No. 163702-07-6).

Typical Physical Properties – Table 1

Data compiled from published information

Not for specification purposes

Properties	Novec 71DA	Freon® TE	Genesolv® 2004	AK-225 AES	4310-SMT
Formulation	Azeotrope ¹	Azeotrope 96% C ₂ Cl ₃ F ₃ 4% Ethanol	Azeotrope 96% CCl ₂ FCH ₃ 4% Methanol	Azeotrope 95.5% C ₃ Cl ₂ HF ₅ 4.5% Ethanol	Azeotrope ²
Boiling Pt °C	40	45	29.4	52	37
Freeze Pt °C	-29 ³	-42	NA	-138	NA
Liquid Density ⁴	1.33	1.50	1.22	1.49	1.35
Surface Tension ⁵	16.4	17.7	18.5	16.8	15.5
Kauri-Butanol Value	33	40	76	41	N/A
Vapor Pressure ⁶	381	362	527	414	486
Viscosity ⁷	0.45	0.65	0.45	0.61	0.49
Heat of Vaporization ⁸	50	43	62	41	50

¹ 52.7% 3M™ Novec™ 7100 Engineered Fluid (C₄F₉OCH₃), 44.6% trans-1,2-dichloroethylene and 2.7% ethanol

² 52.9% HFC-4310 (C₅H₂F₁₀), 43% trans-1,2-dichloroethylene, 4% methanol, 0.1% stabilizer

³ Critical Solution Temperature

⁴ g/ml @ 25°C

⁵ dynes/cm @ 25°C

⁶ mmHg @ 25°C

⁷ cps @ 25°C

⁸ cal/g @ boiling point

N/A-Not Available

Environmental and Safety Properties and Exposure Guidelines – Table 2

Data compiled from published information

Not for specification purposes

Properties	Novec 71DA	Freon® TE	Genesolv® 2004	AK-225 AES	4310-SMT
Ozone Depletion Potential-ODP ¹	0.00	0.77	0.11	0.03	0.00
Global Warming Potential ²	170	5800	670	400	900
Flash Point	None	None	None	None	None

¹ CFC-113 = 1.0

² GWP-100 year ITH, CO₂ = 1.0

³ Vol % by ASTM E681-94 @ 100°C

“Freon” is a registered trademark of DuPont.

“Genesolv” is a registered trademark of Honeywell (formerly AlliedSignal Corp.)

Regulatory Status

The U.S. Environmental Protection Agency (EPA) has listed all components of 3M™ Novec™ 71DA Engineered Fluid as “acceptable,” without restrictions, under the EPA’s Significant New Alternatives Policy (SNAP) program.

Regulations on Chlorine-Containing Solvents – Table 3

Regulation	Trans-1,2-dichloroethylene	Trichloroethylene	Perchloroethylene	Methylene Chloride
VOC Designation	Yes	Yes	Yes	No
Reportable Qty. for Accidental Release	1000 lbs. (2240 lbs. in Novec 71DA)	100 lbs.	100 lbs.	1000 lbs.
Regulated if Emitted into Water	Yes	Yes	Yes	Yes
Hazardous Air Pollutant	No	Yes	Yes	Yes
Annual Reporting (EPCRA 313) (SARA)	No	Yes	Yes	Yes
OSHA List of toxins/carcinogens	No	Yes	Yes	Yes

Regulations and Reporting

Because of its favorable health and environmental properties, trans-1,2-dichloroethylene (t-DCE) is less regulated in the areas noted compared to the other chlorinated solvents in Table 3. Regulations affecting Novec 71DA fluid include VOC emissions of t-DCE and ethanol and reporting requirements if t-DCE is emitted into water or if a spill of 2240 lbs. or more of Novec 71DA fluid occurs. t-DCE is not considered a Hazardous Air Pollutant (HAP) and is not subject to annual reporting requirements.

Environmental Policy

3M will continue to recognize and exercise its responsibility to prevent pollution at the source wherever and whenever possible; develop products that will have a minimal effect on the environment; conserve natural resources through the use of reclamation and other appropriate methods; assure that its facilities and products meet and sustain the regulations of all federal, state and local environmental agencies; assist, wherever possible, governmental agencies and other official organizations engaged in environmental activities.

Safety and Handling

Novec 71DA fluid is nonflammable and does not exhibit flammability characteristics under normal operating and storage conditions. This fluid is highly resistant to thermal breakdown and hydrolysis in storage and during use. Before using this product, please read the current Material Safety Data Sheet available through your 3M sales or technical service representative and the precautionary statement on the product package. Follow all applicable precautions and directions.

Packaging and Availability

Novec 71DA fluid may be ordered in the following container sizes:

- 1-gallon pail
- 5-gallon pail
- 55-gallon drum

Recycle and Disposal Options

Used Fluid Return Program

3M offers a program for free* pickup and return of used 3M specialty fluids in the U.S. through Safety-Kleen Corp. A pre-negotiated handling agreement between users and this service provider offers users broad protection against future liability for used 3M product. The fluid return program is covered by independent third-party financial and environmental audits of treatment, storage and disposal facilities. Necessary documentation is provided. A minimum of 30 gallons of used 3M specialty fluid is required for participation in this free program.*

Safety-Kleen Corp. has a network of 156 branch service centers in the U.S. This large fleet will provide timely, economical fluid disposal service.

For additional information on the 3M Used Fluid Return Program, contact Safety-Kleen at this toll-free line: 1.888.932.2731. Contact your local 3M representative for fluid return programs outside the U.S.

* Must have a 30 or more gallon purchase to participate in the 3M paid program. Used product of 5-30 gallons can be returned through Safety-Kleen at the user's expense.

Resources

3M™ Novec™ Engineered Fluids are supported by global sales, technical and customer service resources, with fully-staffed technical service laboratories in the U.S., Europe, Japan, Latin America and Southeast Asia. Users benefit from 3M's broad technology base and continuing attention to product development, performance, safety and environmental issues.

For additional technical information on 3M™ Novec™ 71DA Engineered Fluid in the United States, call 3M Customer Service, **800 810 8513**.

For information on additional 3M fluids, coatings and other chemical products for the electronics industry, visit our web site at:

www.3M.com/electronics

Product Use: All statements, technical information and recommendations contained in this document are based on tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M Electronics

Building 21-1W-10
900 Bush Avenue
St. Paul, MN 55106

www.3M.com/electronics

3M is a trademark of 3M Company.
Used under license by 3M subsidiaries and affiliates.

Issued: 8/05

© 2005 3M

5045(HB)
98-0212-2611-7